


REF.

- BKNT KS S BK LED DIM0-10V
- BKNT KS S BK LED DIMDALI
- BKNT KS S BK LED DIMBT
- BKNT KS S IV LED DIM0-10V
- BKNT KS S IV LED DIMDALI
- BKNT KS S IV LED DIMBT

REF.

- BKNT KS S NI LED DIM0-10V
- BKNT KS S NI LED DIMDALI
- BKNT KS S NI LED DIMBT
- BKNT KS S GD LED DIM0-10V
- BKNT KS S GD LED DIMDALI
- BKNT KS S GD LED DIMBT

LIGHT SOURCE

Class I 

Dual Circuit - DC: Enables independent dimming and control of the decorative wood shades and the tech downlight.

- 120 - 277V: Dimmable 0-10V or DALI
- 220-240V: Dimmable Bluetooth - BT

Driver:

Constant Current 900mA (shades & downlight)

LED Integrated:

- Led module
- Energy class F

3.000K, CRI>90, 80W, 50-60Hz, 1949 lm*
Available in 2.700K and 4.000K on request

*Measurements obtained by photometric laboratory tests using ivory white shades. Veneer Ref: 20 Ivory White.

PACKAGING

Box Size: 154 x 54 x 11 cm

Box Volume: 0,1 m³

Weight: Gross - 12,6 Kg | Net - 8,4 Kg

MATERIALS & COMPONENTS





8 Wood Veneer Shades

Metal Structure & Canopy





4 Electrified Black Steel Cables: 2,5m drop

FINISHES

WOOD VENEER

-  20 Ivory White
-  22 Natural Beech
-  21 Natural Cherry
-  29 Grey

METAL

-  BK-Matte Black
-  NI-Matte Nickel
-  IV-Matte Ivory
-  GD-Gold